



The content of barrier resin depends on the customer's requirements.

The thickness of the middle layer depends on the amount of barrier material.

When the preform is cut below the support ring and above the gate pad split line, the barrier weight distribution is 50% in each half with a tolerance of +/-5% in each half.

The position of the Leading Edge is placed at the height of the support ring with a range of +/-5mm.

Position of the Trailing Edge must be at height of the gate pad split line for definite.

A positioning of the Trailing Edge below the gate pad split line is also acceptable but for not more than 6mm.

Material: PET			
Gewicht: 18g±0.5			
Gewinde: 38mm Bericap 3Start			
	Datum	Name	Maßstab
gez.	05.02.14	IG	1:1
gepr.	05.02.14	MR	
Für diese Zeichnung behalten wir uns alle Rechte vor. Ohne unsere vorherige ausdrückliche Genehmigung darf sie weder vervielfältigt noch Dritten zugänglich gemacht werden, sie darf auch durch den Empfänger oder Dritte nicht in anderer Weise mißbräuchlich verwendet werden.			



PET-Verpackungen GmbH  
Deutschland  
Gewerbegebiet 4  
D-98701 Großbreitenbach

Benennung:

Preform 18g  
Bericap 3 Start Multilayer

Zeichn. Nr.:

PET14\_009\_00

Formen Nr.:

PEVEDE 53/XX